

**SUBMITTAL SHEET**

**System 3100B** Uninsulated Flexible Connectors

|                           |  |  |
|---------------------------|--|--|
| <b>CORE TYPE</b>          | 2 Ply, Polyester - Polyester Film                                |  |
| <b>TEMPERATURE RANGE</b>  | -20° F to 250° F.  |  |
| <b>SIZES IN DIAMETER</b>  | 2 / 3 / 4 / 5 / 6 / 7 / 8 / 9 / 10 / 11 / 12 / 14 / 16 / 18 / 20 |  |
| <b>LENGTH IN FEET</b>     | Standard 25ft; Custom 4ft -30ft                                  |  |
| <b>INSIDE BEND RADIUS</b> | 2 / 3 / 4 / 5 / 6 / 7 / 8 / 9 / 10 / 11 / 12 / 14 / 16 / 18 / 20 |  |
| <b>STEEL WIRE</b>         | Zinc coated spring steel wire helix                              |  |
| <b>RATED VELOCITY</b>     | 4000 fpm.  |  |
| <b>MAX RATED PRESSURE</b> | <b>POSITIVE</b>  | 6" W.C. (2" – 10" Dia.) 4" W.C. (12"-20" Dia.) |
|                           | <b>NEGATIVE</b>  | ½" W.C. (2" – 20" Dia.)                        |



|                          |                      |
|--------------------------|----------------------|
| JOB _____                |                      |
| LOCATION _____           | JOB NO. _____        |
| ENGINEER _____           | JOB NO. _____        |
| CONTRACTOR _____         | REPRESENTATIVE _____ |
| <b>Certified Correct</b> |                      |
| BY _____                 | BY _____             |
| TITLE _____              | TITLE _____          |
| DATE _____               | DATE _____           |